

AB301

Mid power beacon - amber lens

The range of low and high profile XENON beacons offers maximum light output and high efficiency for use in 10-15 V intruder alarms. Tested for IP65 rating, with polycarbonate lenses as standard, they are suitable for the most demanding applications.



Details

- Maximum light output
- High efficiency

- Tested to IP65 rating
- Polycarbonate lens

AB301

Mid power beacon - amber lens

Technical Specifications

General

Accessory group	Beacon
Type	Accessory

Electrical

Operating voltage	12 V
Power consumption	1 W
Current consumption	115 mA

Physical

Physical dimensions	75 x 51 mm
---------------------	------------

Environmental

Operating temperature	-30 to 70°C
IP rating	IP65

Power supply

10 to 15 VDC

Current consumption

115 mA

Power output

1 W

Flash energy

0.9 nominal J

Flash frequency

60 flashes/min

Electrical connections

2 leads

Installation

Mounting base included

Base colour

White

Lens colour

Amber

Dimensions (Ø x H)

75 x 51 mm

Operating temperature

-30 to +70°C

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

6 December 2018 - 12:22 PM

